

### M22M-IT-D22



Features					
Resolution	Memory	Video Ring Buffer	Sensitivity	Housing	Color
640x480	64 MB	32 MB	0.05 lux	Reinf. Plastic	white

Variations					
Outdoor	Indoor	Mono	Dual	Day	Night
x	X	x		x	



Outdoor weatherproof (IP65)  
(-30°C to +60°C, -22°F to +140°F)

### Features

Resolution	<b>VGA</b> , CMOS 640x480 color, sensitivity: 1 lux (t = 1/60 sec) / 0.05 lux (t = 1/1 sec), image formats: 640x480, 320x240, 160x120 pixels
Standard Lens	<b>L22 Super Wide Angle 90°</b> (90° x 67°); f = 4 mm (equiv. ~22 mm on 35 mm systems); in 10 m: approx. 20 m x 13.3 m
Max. Frame Rate	<b>30 fps VGA • 30 fps CIF</b>
Interfaces	10/100 Ethernet (RJ45), USB master (for MX expansion modules)
Sensors	Video motion detection, exposure windows, microphone, speaker
Features	Web server, FTP client, e-mail, MultiView, recorder/player, softbuttons, IP Notify (send, receive) for external management systems, integrated VoIP from/to the browser, SIP video telephony and alarm messaging, IP announcement, PDA web pages, MxPEG Live, logo generator, snapshot recording (10 pre-, 10 post-alarm images), video audio recording (30 fps VGA), video audio recording (events), video audio recording (scheduled)
Video Ring Buffer	<b>32 MB</b> internal image/event storage (approx. 2,000 images 320x240, high quality); event- and time-controlled storage: internal, via FTP on web server or <b>PC on the LAN</b> (Windows/Linux NFS/Mac); images are directly accessible, no FTP required (although possible)
Optional Accessories	 External power supply (MX-NPA-Set) is only required if power is not supplied using <b>PoE</b>
Dimensions	With SecureFlex in wall mount position: 137 x 150 x 200 mm (WxHxD) With SecureFlex in ceiling mount position: 137 x 200 x 187 mm (WxHxD)
Standard Delivery	 Weatherproof housing (IP65) made of fiberglass-reinforced plastic (PBT-30GF), white metallic, L22 Super Wide Angle lens, Polycarbonate lens cover, spare lens cover, manual, patch cable S/FTP white 8-wire 50 cm (double-shielded), Allen wrench, SecureFlex mount with concealed cabling, covers RJ45 wall outlets, stainless steel mounting set
Warranty	12 months

Article Number	Details	MSRP	Euro
MX-M22M-IT-D22	In/Outdoor <b>VGA Mono</b> , incl. Super Wide Angle Day (22mm)	Stock	598