

M22M-Sec



Features					
Resolution	Memory	Video Ring Buffer	Sensitivity	Housing	Color
1280x960	128 MB	64 MB	0.05 lux	Reinf. Plastic	white

Variations					
Outdoor	Indoor	Mono	Dual	Day	Night
x	X	x		x	



Outdoor weatherproof (IP65)
(-30°C to +60°C, -22°F to +140°F)

Features

Resolution	<i>MEGA</i> , CMOS 1280x960 color, sensitivity: 1 lux (t = 1/60 sec) / 0.05 lux (t = 1/1 sec), image formats: 1280x960, 640x480, 320x240, 160x120 pixels, custom formats (e.g. 1000x400) <i>Zoom</i> : Digital zoom 1x, 2x, 4x, software panning/tilting
Standard Lens	<i>All lens options available!</i> L22 Super Wide Angle 22 mm (90°Hx67°V; in 10m: 20m x 13.3 m), L32 wide-angle 32 mm (60°Hx45°V, in 10m: 11.5m x 8.2m), L43 wide-angle 43 mm (45°Hx34°V, in 10m: 8.2m x 6.1m), L65 tele 65 mm (31°Hx23°V, in 10m: 5.5m x 4.0m), L135 tele 135 mm (15°Hx11°V, in 10m: 2.6m x 1.9m)
Max. Frame Rate	<i>30 f ps VGA • 30 f ps CIF • 10 f ps MEGA</i>
Interfaces	10/100 Ethernet (RJ45), USB master (for MX expansion modules)
Sensors	Video motion detection, exposure windows, microphone, speaker
Features	Web server, FTP client, e-mail, MultiView, recorder/player, softbuttons, IP Notify (send, receive) for external management systems, integrated VoIP from/to the browser, SIP video telephony and alarm messaging, IP announcement, PDA web pages, MxPEG Live, logo generator, snapshot recording (50 pre-, 50 post-alarm images), video audio recording (30 fps VGA), video audio recording (events), video audio recording (scheduled); <i>Secure Extras</i> : scheduled privacy zones, flexible event logic, Master/Slave arming
Video Ring Buffer	<i>64 MB</i> internal image/event storage (approx. 4,000 images 320x240, high quality); event- and time-controlled storage: internal, via FTP on web server or <i>PC on the LAN</i> (Windows/Linux NFS/Mac); images are directly accessible, no FTP required (although possible)
Optional Accessories	 External power supply (MX-NPA-Set) is only required if power is not supplied using <i>PoE</i>
Dimensions	With SecureFlex in wall mount position: 137 x 150 x 200 mm (WxHxD) With SecureFlex in ceiling mount position: 137 x 200 x 187 mm (WxHxD)
Standard Delivery	 Weatherproof housing (IP65) made of fiberglass-reinforced plastic (PBT-30GF), white metallic, Polycarbonate lens cover, spare lens cover, manual, patch cable S/FTP white 8-wire 50 cm (double-shielded), Allen wrench, SecureFlex mount with concealed cabling, covers RJ45 wall outlets, stainless steel mounting set
Warranty	12 months

Article Number	Details	MSRP	Euro
MX-M22M-Sec	In/Outdoor <i>MEGA Mono</i> , excl. lens	Stock	738
MX-OPT14-L22	L22 Super Wide Angle 22 mm (90°Hx67°V; in 10m: 20.0m x 13.3m)	Stock	60
MX-OPT14-L32	L32 wide-angle 32 mm (60°Hx45°V; in 10m: 11.5m x 8.2m)	Stock	60
MX-OPT14-L43	L43 wide-angle 43 mm (45°Hx34°V, in 10m: 8.2m x 6.1m)	Stock	60
MX-OPT14-L65	L65 tele 65 mm (31°Hx23°V; in 10m: 5.5m x 4.0m)	Stock	60
MX-OPT14-L135	L135 tele 135 mm (15°Hx11°V, in 10m: 2.6m x 1.9m)	Stock	60